



Signalling switch ready to switch-on, 1W

Part no. +IZMX-LCS-1
Article no. 184103
Catalog No. 67C2814G23

Delivery program

Product range			Accessories
Accessories			Auxiliary contact
Accessories			Operational readiness indicator
			1 changeover contact
For use with			IZMX16..., IZMX40... INX16..., INX40...
Instructions			For signaling availability. Alternatively, also for automatic closing upon availability.
			1 changeover contact

Technical data

Rated breaking capacity

Inductive load			
250 V AC		A	10
125 V DC		A	0.5
250 V DC		A	0.25

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	70

Technical data ETIM 6.0

Low-voltage industrial components (EG000017) / Auxiliary contact block (EC000041)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Auxiliary switch block (ecI@ss8.1-27-37-13-02 [AKN342010])			
Number of contacts as change-over contact			1
Number of contacts as normally open contact			0
Number of contacts as normally closed contact			0
Rated operation current I _e at AC-15, 230 V		A	10
Type of electric connection			Flat plug-in connection
Model			Half-integrated
Mounting method			-