



## Automatic reset reclosing lockout

**Part no.** +IZMX-RA-1  
**Article no.** 184119  
**Catalog No.** 67C2825G02

### Delivery program

|               |  |  |   |
|---------------|--|--|---|
| Product range |  |  | Accessories   |
| Accessories   |  |  | Trip indication / Reset options   |
| Accessories   |  |  | Automatic reset   |
|               |  |  | The switch does not contain the mechanical trip-indicator (red pin).<br>The switch can be switched on again immediately after a trip.<br>Can be used in combination with Overload Trip Switches.<br>Cannot be combined with remote reset. |
| For use with  |  |  | IZMX16..., IZMX40...  |

### Design verification as per IEC/EN 61439

|  |  |    |     |
|--|--|----|-----|
| Technical data for design verification |  |    |     |
| Operating ambient temperature min.     |  | °C | -25 |
| Operating ambient temperature max.     |  | °C | 70  |

### Technical data ETIM 6.0

|   |  |  |   |
|---|--|--|---|
| Low-voltage industrial components (EG000017) / Accessories for low-voltage switch technology (EC002498)   |  |  |   |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Low-voltage switch technology (accessories) / Component for low-voltage switch technology (accessories) (ecI@ss8.1-27-37-92-01 [AKN570010]) |  |  |   |
| Type of accessory   |  |  | - |