



House service fuse-link, low voltage, 100 A, AC 415 V, BS system C type II,
23 x 57 mm, gL/gG, BS



Powering Business Worldwide™

Article no. **100KR85**
Catalog No. **100KR85**

Delivery program

Product range			Fuse
Basic function			House service fuse-link
Field of application			low voltage
Rated current	I	A	100
Rated voltage			AC 415 V
Construction size			BS system C type II
Size			23 x 57 mm
Utilization category			gL/gG
Breaking Capacity		kA	33
usable for size/applications			protection of incoming cables into residential and commercial properties
Standard/Approval			BS
Shape			cylindrical
Standards/Regulations			BS88-3
Optional accessories			house-service cut-out 6080SP

Technical data ETIM 6.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss8.1-27-14-20-02 [AFZ797010])			
Size			-
Rated voltage			-
Nominal current		A	100
With striker			No

Additional product information (links)

Product datasheet (pdf)	http://www1.cooperbusmann.com/pdf/f5b2e5d9-2ddd-4332-bbb2-0f03ca7cf10e.pdf
-------------------------	---