



Fuse-link, LV, 100 A, AC 660 V, DC 460 V, BS88/A4, 26 x 110 mm, gM, BS, 100M125

Article no. TCP100M125
Catalog No. TCP100M125A

Similar to illustration

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	100
Motor current rating	I	A	100M125
Rated voltage			AC 660 V DC 460 V
Construction size			BS88/A4
Size			26 x 110 mm
Utilization category			gM
Description			motor-rated
Breaking Capacity		kA	80
usable for size/applications			general industrial applications
Standard/Approval			BS
Shape			offset bolted tags (slotted)
Standards/Regulations			BS88-2 IEC 60269-2
Optional accessories			fuse-holder RS100

Technical data ETIM 6.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss8.1-27-14-20-05 [AFZ800012])			
Construction size			-
Nominal rated current		A	100
Nominal rated voltage		V	660
Utilization category			-
Type of fuse status indicator			None

Additional product information (links)

Product datasheet (pdf)	http://www1.cooperbusmann.com/pdf/0bed7fd6-7dbd-4d9c-a937-9d817ce5c100.pdf
-------------------------	---