



Fuse-link, LV, 160 A, AC 415 V, BS88, 31 x 110 mm, gL/gG, BS

Article no. DE0160
Catalog No. DE0160

Similar to illustration

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	160
Rated voltage			AC 415 V
Construction size			BS88
Size			31 x 110 mm
Utilization category			gL/gG
Breaking Capacity		kA	80
usable for size/applications			general industrial applications
Standard/Approval			BS
Shape			offset bolted tags
Standards/Regulations			BS88 IEC 60269

Technical data ETIM 6.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss8.1-27-14-20-05 [AFZ800012])			
Construction size			-
Nominal rated current		A	160
Nominal rated voltage		V	415
Utilization category			gL/gG (cable protection/equipment protection)
Type of fuse status indicator			None

Additional product information (links)

Product datasheet (pdf)	http://www1.cooperbusmann.com/pdf/047ae41a-0eb3-4880-be3b-9ee65fccc91b.pdf
-------------------------	---