



Fuse-link, LV, 20 A, AC 440 V, BS88/A1, 14 x 56 mm, gM, BS, 20M25

Article no. NIT20M25
Catalog No. NIT20M25

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	20
Motor current rating	I	A	20M25
Rated voltage			AC 440 V
Construction size			BS88/A1
Size			14 x 56 mm
Utilization category			gM
Description			motor-rated
Breaking Capacity		kA	80
usable for size/applications			general industrial applications
Standard/Approval			BS
Shape			offset bolted tags (slotted)
Standards/Regulations			BS88-2 IEC 60269-2
Optional accessories			fuse-holder CM32FC and RS20

Technical data ETIM 6.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss8.1-27-14-20-05 [AFZ800012])			
Construction size			-
Nominal rated current		A	20
Nominal rated voltage		V	440
Utilization category			-
Type of fuse status indicator			None

Additional product information (links)

Product datasheet (pdf)	http://www1.cooperbussmann.com/pdf/0bed7fd6-7dbd-4d9c-a937-9d817ce5c100.pdf
-------------------------	---