



Fuse-link, LV, 250 A, AC 660 V, DC 460 V, BS88/B3, 40 x 137 mm, gL/gG, BS



Powering Business Worldwide™

Article no. TKF250
Catalog No. TKF250

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	250
Rated voltage			AC 660 V DC 460 V
Construction size			BS88/B3
Size			40 x 137 mm
Utilization category			gL/gG
Breaking Capacity		kA	80
usable for size/applications			general industrial applications
Standard/Approval			BS
Shape			centre-bolted tags
Standards/Regulations			BS88-2 IEC 60269-2

Technical data ETIM 6.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss8.1-27-14-20-05 [AFZ800012])			
Construction size			-
Nominal rated current		A	250
Nominal rated voltage		V	660
Utilization category			gL/gG (cable protection/equipment protection)
Type of fuse status indicator			None

Additional product information (links)

Product datasheet (pdf)	http://www1.cooperbusmann.com/pdf/3e2cace6-400d-4026-af91-49c5a8d88159.pdf
-------------------------	---