## Fuse-link, LV, 30 A, AC 240 V, BS1361, 13 x 29 mm, BS





Article no. C3030 Catalog No. C3030

**Delivery program** 

| Product range                |   |    | Fuse          |
|------------------------------|---|----|---------------|
| Basic function               |   |    | Fuse-link     |
| Field of application         |   |    | low voltage   |
| Rated current                | I | Α  | 30            |
| Rated voltage                |   |    | AC 240 V      |
| Construction size            |   |    | BS1361        |
| Size                         |   |    | 13 x 29 mm    |
| Breaking Capacity            |   | kA | 16.5          |
| usable for size/applications |   |    | consumer unit |
| Standard/Approval            |   |    | BS            |
| Shape                        |   |    | cylindrical   |
| Standards/Regulations        |   |    | BS1361        |

## **Technical data ETIM 6.0**

| Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)  |   |    |  |  |  |  |
|--|---|----|--|--|--|--|
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss8.1-27-14-20-02 [AFZ797010]) |   |    |  |  |  |  |
| Size   |   | -  |  |  |  |  |
| Rated voltage  |   | -  |  |  |  |  |
| Nominal current  | А | 30 |  |  |  |  |
| With striker   |   | No |  |  |  |  |