

Article no. **CH30J2**  
 Catalog No. **CH30J2**

## Delivery program

|                       |   |    |                      |
|-----------------------|---|----|----------------------|
| Product range         |   |    | Fuse accessory       |
| Basic function        |   |    | Fuse-holder          |
| Rated current         | I | A  | 30                   |
| Rated voltage         |   |    | AC 600 V<br>DC 600 V |
| Construction size     |   |    | UL Class J           |
| Size                  |   |    | 65 x 72 x 117 mm     |
| Description           |   |    | Panel Mounting       |
| Protection            |   |    | IP20                 |
| Breaking Capacity     |   | kA | 200                  |
| Number of poles       |   |    | 2P                   |
| Standard/Approval     |   |    | UL<br>CSA            |
| Standards/Regulations |   |    | UL 512               |

## Technical data ETIM 6.0

|   |  |   |    |
|---|--|---|----|
| Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse base (EC000067)  |  |   |    |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse systems / Low-Voltage HRC fuse base (ecl@ss8.1-27-14-21-06 [AKE278010]) |  |   |    |
| Construction size   |  |   | -  |
| Number of poles   |  |   | 2  |
| Nominal rated current   |  | A | 30 |
| Bus-mounting type   |  |   | No |
| Swivelling mechanism  |  |   | No |