



Fuse-link, LV, 63 A, AC 500 V, BS88/A3, 21 x 87 mm, gM, BS, 63M100

Article no. BA063M100
Catalog No. BA063M100

Similar to illustration

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	63
Motor current rating	I	A	63M100
Rated voltage			AC 500 V
Construction size			BS88/A3
Size			21 x 87 mm
Utilization category			gM
Description			motor-rated
Breaking Capacity		kA	80
usable for size/applications			general industrial applications
Standard/Approval			BS
Shape			offset bolted tags
Standards/Regulations			BS88-2 IEC 60269-2
Optional accessories			fuse-holder CM63F RS63

Technical data ETIM 6.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss8.1-27-14-20-05 [AFZ800012])			
Construction size			-
Nominal rated current		A	63
Nominal rated voltage		V	500
Utilization category			-
Type of fuse status indicator			None

Additional product information (links)

Product datasheet (pdf)	http://www1.cooperbusmann.com/pdf/90feb85f-7af5-43ee-8616-04f9aea2232d.pdf
-------------------------	---