



## Phase busbar, 3-phase, 16qmm, fork connector, 1m



Powering Business Worldwide™

**Part no.** BB-EVF-16/3P-2MU  
**Article no.** 168851  
**Catalog No.** BB-EVF-16/3P-2MU

Similar to illustration

### Delivery program

Basic function			Busbar
Basic function accessories			Busbar for residual-current circuit-breakers Busbar for combined residual-current/power circuit-breaker Busbar for miniature circuit-breaker Busbar for TVSS
Application			Switchgear for industrial and advanced commercial applications
Busbar type			Three-phase
Product range			BB-EV

### Technical data ETIM 6.0

Low-voltage industrial components (EG000017) / Phase busbar (EC000215)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar (ecl@ss8.1-27-37-13-06 [ACN992008])			
Number of phases			3
Number of poles			3
Suitable for number of devices			0
Pitch dimensions		mm	36
Cross section		mm <sup>2</sup>	16
Length		mm	1000
Number of modular spacings			2
Rated permanent current I <sub>u</sub>		A	80
Type of electric connection			Fork
Insulated			Yes
Rated surge voltage		kV	4.5
Conditioned rated short-circuit current I <sub>q</sub>		kA	0
Max. rated operation voltage U <sub>e</sub>		V	690
Rated short-time withstand current I <sub>cw</sub>		kA	0
Suitable for devices with N-busbar			No
Suitable for devices with auxiliary switch			No