



Fuse-link, LV, 7 A, AC 500 V, 10 x 38 mm, 13/32 x 1-1/2 inch, supplemental, UL, time-delay

Article no. FNQ-7
Catalog No. FNQ-7

Similar to illustration

Delivery program

| | | | |
|------------------------------|-------|---|---|
| Product range | | | Fuse |
| Basic function | | | Fuse-link |
| Field of application | | | low voltage |
| Rated current | I | A | 7 |
| Rated voltage | | | AC 500 V |
| Size | | | 10 x 38 mm 13/32 x 1-1/2 inch |
| Utilization category | | | supplemental |
| Description | | | colour-coded |
| usable for size/applications | | | for motor control transformers and circuits with in-rush currents |
| Release characteristic | class | | time-delay |
| Standard/Approval | | | UL |
| Shape | | | cylindrical |
| Material | | | fiber tube construction nickel-plated brass endcaps |

Technical data ETIM 6.0

| | | | |
|--|--|---|----------|
| Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704) | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss8.1-27-14-20-02 [AFZ797010]) | | | |
| Size | | | 10x38 mm |
| Rated voltage | | | - |
| Nominal current | | A | 7 |
| With striker | | | No |

Additional product information (links)

| | |
|-------------------------|---|
| Product datasheet (PDF) | http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-a/Bus_Ele_DS_1012_FNQ.pdf |
|-------------------------|---|