



Fuse-link, LV, 0.8 A, AC 500 V, 10 x 38 mm, 13/32 x 1-1/2 inch, supplemental, UL, time-delay

Article no. FNQ-8-10
Catalog No. FNQ-8/10

Similar to illustration

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	0.8
Rated voltage			AC 500 V
Size			10 x 38 mm 13/32 x 1-1/2 inch
Utilization category			supplemental
Description			colour-coded
usable for size/applications			for motor control transformers and circuits with in-rush currents
Release characteristic	class		time-delay
Standard/Approval			UL
Shape			cylindrical
Material			fiber tube construction nickel-plated brass endcaps

Technical data ETIM 6.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss8.1-27-14-20-02 [AFZ797010])			
Size			10x38 mm
Rated voltage			-
Nominal current		A	0.8
With striker			No

Additional product information (links)

Product datasheet (PDF)	http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-a/Bus_Ele_DS_1012_FNQ.pdf
-------------------------	---