



**Fuse-link, low voltage, 50 A, AC 500 V, NH00, gL/gG, IEC, dual indicator, live gripping lugs**

**Article no. 50NHG00B**  
**Catalog No. 50NHG00B**

## Delivery program

|                       |   |    |  |
|-----------------------|---|----|--|
| Product range         |   |    | Fuse   |
| Basic function        |   |    | Fuse-link  |
| Field of application  |   |    | low voltage  |
| Rated current         | I | A  | 50   |
| Rated voltage         |   |    | AC 500 V   |
| Construction size     |   |    | NH00   |
| Utilization category  |   |    | gL/gG  |
| Status indicator      |   |    | dual indicator                                       |
| Description           |   |    | live gripping lugs                                   |
| Breaking Capacity     |   | kA | 120  |
| Standard/Approval     |   |    | IEC  |
| Shape                 |   |    | square body with knife blade contacts                |
| Standards/Regulations |   |    | IEC 60269-2 fuse system A<br>DIN 43620<br>VDE 0636-2 |
| Optional accessories  |   |    | fuse-holder SD00-D and SD00-S                        |

## Technical data ETIM 6.0

|  |  |   |   |
|--|--|---|---|
| Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)  |  |   |   |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss8.1-27-14-20-05 [AFZ800012]) |  |   |   |
| Construction size  |  |   | NH00  |
| Nominal rated current  |  | A | 50  |
| Nominal rated voltage  |  | V | 500   |
| Utilization category   |  |   | gL/gG (cable protection/equipment protection) |
| Type of fuse status indicator  |  |   | Combination fuse status indicator             |

## Additional product information (links)

|                         |   |
|-------------------------|---|
| Product datasheet (pdf) | <a href="http://www1.cooperbusmann.com/pdf/7878dac4-436b-436a-9672-82f64809b5a2.pdf">http://www1.cooperbusmann.com/pdf/7878dac4-436b-436a-9672-82f64809b5a2.pdf</a> |
|-------------------------|---|