



Fuse-link, LV, 50 A, AC 400 V, NH02, gL/gG, IEC, dual indicator, insulated gripping lugs

**Article no.** 50NHG02BI-400  
**Catalog No.** 50NHG02BI-400

Similar to illustration

## Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	50
Rated voltage			AC 400 V
Construction size			NH02
Utilization category			gL/gG
Status indicator			dual (combination) indicator system
Description			insulated gripping lugs
Breaking Capacity		kA	120
Standard/Approval			IEC
Shape			square body with knife blade contacts
Standards/Regulations			IEC 60269-2 fuse system A DIN 43620 VDE 0636-2

## Technical data ETIM 6.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss8.1-27-14-20-05 [AFZ800012])			
Construction size			-
Nominal rated current		A	50
Nominal rated voltage		V	400
Utilization category			gL/gG (cable protection/equipment protection)
Type of fuse status indicator			Combination fuse status indicator

## Additional product information (links)

Product datasheet (PDF)	<a href="http://www1.cooperbusmann.com/pdf/1d43a21b-d2a9-476a-8090-9972b467e943.pdf">http://www1.cooperbusmann.com/pdf/1d43a21b-d2a9-476a-8090-9972b467e943.pdf</a>
-------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------