



Fuse-link, LV, 630 A, AC 400 V, NH3, gL/gG, IEC, dual indicator, live gripping lugs

Article no. **630NHG3B-400**
Catalog No. **630NHG3B-400**

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	630
Rated voltage			AC 400 V
Construction size			NH3
Utilization category			gL/gG
Status indicator			dual (combination) indicator system
Description			live gripping lugs
Breaking Capacity		kA	120
Standard/Approval			IEC
Shape			square body with knife blade contacts
Standards/Regulations			IEC 60269-2 fuse system A DIN 43620 VDE 0636-2

Technical data ETIM 6.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss8.1-27-14-20-05 [AFZ800012])			
Construction size			NH3
Nominal rated current		A	630
Nominal rated voltage		V	400
Utilization category			gL/gG (cable protection/equipment protection)
Type of fuse status indicator			Combination fuse status indicator

Additional product information (links)

Product datasheet (PDF)	http://www1.cooperbusmann.com/pdf/1d43a21b-d2a9-476a-8090-9972b467e943.pdf
-------------------------	---