



Fuse-link, LV, 800 A, AC 440 V, NH3, gL/gG, IEC, dual indicator, live gripping lugs

Article no. **800NHG3B**
Catalog No. **800NHG3B**

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	800
Rated voltage			AC 440 V
Construction size			NH3
Utilization category			gL/gG
Status indicator			dual (combination) indicator system
Description			live gripping lugs
Breaking Capacity		kA	120
Standard/Approval			IEC
Shape			square body with knife blade contacts
Standards/Regulations			IEC 60269-2 fuse system A DIN 43620 VDE 0636-2

Technical data ETIM 6.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss8.1-27-14-20-05 [AFZ800012])			
Construction size			NH3
Nominal rated current		A	800
Nominal rated voltage		V	440
Utilization category			gL/gG (cable protection/equipment protection)
Type of fuse status indicator			Combination fuse status indicator

Additional product information (links)

Product datasheet (pdf)	http://www1.cooperbusmann.com/pdf/47d91307-3679-4278-9b4d-f863987a8c2d.pdf
-------------------------	---