



Fuse-link, LV, 800 A, AC 690 V, NH4, gL/gG, IEC, single indicator, live gripping lugs

Article no. 800NHG4B-690
Catalog No. 800NHG4B-690

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	800
Rated voltage			AC 690 V
Construction size			NH4
Utilization category			gL/gG
Status indicator			single (top) indicator system
Description			live gripping lugs
Standard/Approval			IEC
Shape			square body with slotted blade contacts
Standards/Regulations			IEC 60269-2 fuse system A DIN 43620 VDE 0636-2

Technical data ETIM 6.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss8.1-27-14-20-05 [AFZ800012])			
Construction size			NH4
Nominal rated current		A	800
Nominal rated voltage		V	690
Utilization category			gL/gG (cable protection/equipment protection)
Type of fuse status indicator			Top fuse status indicator

Additional product information (links)

Product datasheet (PDF)	http://www.cooperindustries.com/content/dam/public/bussmann/iec-electrical/resources/data-sheets/bus-iec-ds-720109-nh690vfuselinks.pdf
-------------------------	---