

**Part no.** C445MB-072V  
**Article no.** 181567  
**Catalog No.** C445MB-072V

## Delivery program


Product range			Measurement modules
Basic function			Current measurement Voltage measurement
Current range		A	9 - 72
Mounting width		mm	55

## Technical data

### General

Standards			IEC/EN 60947-4-1, UL 60947-4-1
Ambient temperature			
Open		°C	-40 - +60
Mounting position			As required
Mechanical shock resistance		g	15 Shock duration 11 ms non-operating
Degree of Protection			IP20

### Main conducting paths

Rated insulation voltage	$U_i$	V AC	110 - 690
Short-circuit protection max. fuse gL-characteristic		A gL	160
Current heat loss (3 conductors)			
Maximum setting		W	5
Push-through opening		mm	10.5

## Design verification as per IEC/EN 61439

Technical data for design verification			
Static heat dissipation, non-current-dependent	$P_{vs}$	W	5
Operating ambient temperature min.		°C	-40
Operating ambient temperature max.		°C	60

## Technical data ETIM 6.0

Low-voltage industrial components (EG000017) / Current transformer (EC002048)			
Electric engineering, automation, process control engineering / Signal processing / Transformer / Current transformer (ecl@ss8.1-27-21-09-02 [AAB626011])			
Model			Through-feed current converter
Primary rated current		A	72
Secondary rated current		A	0
Secondary rated apparent power		VA	0
Accuracy class			2
Over voltage limiting factor			-
Calibrated			No
With shock protection			Yes
Opening height		mm	10,5
Opening width		mm	10,5
Opening diameter		mm	10,5
Snap mounting			Yes
With copper rail			No
Secondary connection			Plug-in connection
Number of primary inputs			3