

Fused disconnector, low voltage, 30 A, AC 600 V, CC, 2P, UL



Article no. CCP-2-30CC Catalog No. CCP-2-30CC

Delivery program

Product range			Control
Basic function			Fused disconnector
Field of application			low voltage
Rated current	I	Α	30
Rated voltage			AC 600 V
Construction size			CC
Protection			IP20
Breaking Capacity		kA	200
Number of poles			2P
usable for size/applications			fuse-links LP-CC, FNQ-R, KTK-R
Standard/Approval			UL
Standards/Regulations			UL 98

Technical data ETIM 6.0

Low-voltage industrial components (EG000017) / Fuse switch disconnector (EC001040)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Fuse switch disconnector (aci@scs 1-27-37-14-01 [AKE058010])

(ecl@ss8.1-27-37-14-01 [AKF058010])	3,,	
Version as main switch		No
Version as safety switch		No
Max. rated operation voltage Ue AC	V	600
Rated permanent current lu	Α	30
Rated operation power at AC-23, 400 V	kW	12
Conditioned rated short-circuit current Iq	kA	200
Rated short-time withstand current lcw	kA	200
Suitable for fuses		
Number of poles		2
With error protection		No
Type of electrical connection of main circuit		Screw connection
Suitable for ground mounting		No
Suitable for front mounting 4-hole		No
Suitable for busbar mounting		Yes
Type of control element		Rocker lever
Position control element		Front side
Motor drive optional		No
Motor drive integrated		No
Version as emergency stop installation		No
Degree of protection (IP), front side		IP20

Additional product information (links)

Product datasheet (pdf)	$http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-b/Bus_Ele_DS_1157_CCP.pdf$
Product datasheet (web)	http://www.cooperindustries.com/content/public/en/bussmann/electrical/products/disconnects/ccp-family/midget_10x38_up_to30a.html