



Fuse-link, LV, 125 A, AC 400 V, 22 x 58 mm, aM, IEC, indicating

**Article no.** C22M125I  
**Catalog No.** C22M125I

Similar to illustration

## Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	125
Rated voltage			AC 400 V
Size			22 x 58 mm
Utilization category			aM
Status indicator			with indicator
Breaking Capacity		kA	120
Standard/Approval			IEC
Shape			cylindrical
Standards/Regulations			IEC 60269-2

## Technical data ETIM 6.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss8.1-27-14-20-02 [AFZ797010])			
Size			22x58 mm
Rated voltage			AC 400 V
Nominal current		A	125
With striker			No

## Additional product information (links)

Product datasheet (pdf)	<a href="http://www1.cooperbusmann.com/pdf/7eba542b-1b11-4a86-afd0-69ed8f8a374b.pdf">http://www1.cooperbusmann.com/pdf/7eba542b-1b11-4a86-afd0-69ed8f8a374b.pdf</a>
-------------------------	---