



Fuse-link, LV, 50 A, AC 690 V, 22 x 58 mm, aM, IEC, indicating

**Article no.** C22M50I  
**Catalog No.** C22M50I

Similar to illustration

## Delivery program

|                       |   |    |                |
|-----------------------|---|----|----------------|
| Product range         |   |    | Fuse           |
| Basic function        |   |    | Fuse-link      |
| Field of application  |   |    | low voltage    |
| Rated current         | I | A  | 50             |
| Rated voltage         |   |    | AC 690 V       |
| Size                  |   |    | 22 x 58 mm     |
| Utilization category  |   |    | aM             |
| Status indicator      |   |    | with indicator |
| Breaking Capacity     |   | kA | 80             |
| Standard/Approval     |   |    | IEC            |
| Shape                 |   |    | cylindrical    |
| Standards/Regulations |   |    | IEC 60269-2    |

## Technical data ETIM 6.0

|  |  |   |          |
|--|--|---|----------|
| Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)  |  |   |          |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss8.1-27-14-20-02 [AFZ797010]) |  |   |          |
| Size   |  |   | 22x58 mm |
| Rated voltage  |  |   | AC 690 V |
| Nominal current  |  | A | 50       |
| With striker   |  |   | No       |

## Additional product information (links)

|                         |   |
|-------------------------|---|
| Product datasheet (pdf) | <a href="http://www1.cooperbusmann.com/pdf/7eba542b-1b11-4a86-afd0-69ed8f8a374b.pdf">http://www1.cooperbusmann.com/pdf/7eba542b-1b11-4a86-afd0-69ed8f8a374b.pdf</a> |
|-------------------------|---|