



Fuse-link, LV, 20 A, AC 400 V, 10 x 38 mm, aM, IEC

Article no. C10M20
Catalog No. C10M20

Delivery program

| | | | |
|------------------------------|---|---|---|
| Product range | | | Fuse |
| Basic function | | | Fuse-link |
| Field of application | | | low voltage |
| Rated current | I | A | 20 |
| Rated voltage | | | AC 400 V |
| Size | | | 10 x 38 mm |
| Utilization category | | | aM |
| usable for size/applications | | | motor protection for industrial applications |
| Standard/Approval | | | IEC |
| Shape | | | cylindrical |
| Standards/Regulations | | | IEC 60269-2 |

Technical data ETIM 6.0

| | | | |
|--|--|---|----------|
| Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704) | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss8.1-27-14-20-02 [AFZ797010]) | | | |
| Size | | | 10x38 mm |
| Rated voltage | | | AC 400 V |
| Nominal current | | A | 20 |
| With striker | | | No |

Additional product information (links)

| | |
|-------------------------|---|
| Product datasheet (PDF) | http://www.cooperindustries.com/content/dam/public/bussmann/iec-electrical/resources/data-sheets/bus-iec-ds-720115-cylindricalfuselinks.pdf |
|-------------------------|---|