

Switch-disconnector, 3p+N, 250A, with shaft and handle

Part no. DMV-250N/1+SH
Article no. 1814421

Technical data ETIM 5.0

Low-voltage industrial components (EG000017) / Switch disconnector (EC000216)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Switch disconnector (ecl@ss8-27-37-14-03 [AKF060009])			
Version as switch disconnector compact			Yes
Version as main switch			No
Version as maintenance-/service switch			No
Version as safety switch			No
Version as emergency stop installation			Yes
Max. rated operation voltage Ue AC	V		690
Rated permanent current Iu	A		250
Rated operation power AC-3, 400 V	kW		0
Rated operation power at AC-23, 400 V	kW		147
Conditioned rated short-circuit current Iq	kA		0
Number of poles			3
Number of auxiliary contacts as normally closed contact			0
Number of auxiliary contacts as normally open contact			0
Number of auxiliary contacts as change-over contact			0
Motor drive optional			No
Motor drive integrated			No
Voltage release optional			No
Device construction			Complete device in housing
Suitable for ground mounting			Yes
Suitable for front mounting			No
Suitable for front mounting center			No
Suitable for distribution board installation			Yes
Suitable for intermediate mounting			No
Type of control element			Long turning handle
Interlockable			No
Connection type main current circuit			Screw connection
Degree of protection (IP), front side			IP20