

Power meter, 3 N, 80 A_x

Powering Business Worldwide*

Part no. EME3P80 Article no. 167413 Catalog No. EME3P80

Technical data ETIM 6.0

| Motore (EC000045) | / Kilowatt-hour meter | (ECOO1EOG) |
|---------------------|-----------------------|------------|
| ivieters (EGUUUU43) | / Knowatt-nour meter | (ECOUTOUD) |

Electric engineering, automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Electronic electricity meter (ecl@ss8.1-27-14-23-16 [AFZ828011])

| (ecl@ss8.1-27-14-23-16 [AFZ828011]) | | |
|-------------------------------------|--------------------|---------------------------------|
| Type of meter | | Electromechanical |
| Rated current (In) | Α | 80 |
| Max. current (Imax) | Α | 6 |
| Rated voltage (Un) N-L | V | 184 - 276 |
| Rated voltage (Un) L-L | V | 319 - 480 |
| Frequency | Hz | 50 - 50 |
| Accuracy class | | В |
| Pole type | | Three conductor |
| Model | | Direct measurement |
| Energy type | | Effective power and blind power |
| Suitable for | | Purchase/supply |
| Tariff type | | Two-tariff |
| Tariff control | | Internal |
| Measuring type load profile | | No |
| Escapement mechanism | | No |
| Calibrated | | No |
| Approval | | Measuring Instruments Directive |
| Pulse output | | Electrical |
| Pulse type | | S0 |
| Pulse rate | Imp/kWh (kvarh) | 0 - 0 |
| Type of indication | | Digital |
| Mounting method | | DRA (DIN-rail adapter) |
| Width in number of modular spacings | | 4.1 |
| Type of interface | | |
| EEC40 signature | | No |
| With lock code | | Yes |
| Number of positions total (counter) | | 8 |
| Degree of protection (IP) | | IP20 |
| | | |