



## Residual current circuit breaker (RCCB), 125A, 2p, 100mA, type G/A

**Part no.** FRCMM-125/2/01-G/A  
**Article no.** 171169  
**Catalog No.** FRCMM-125/2/01-G/A

Similar to illustration

## Delivery program

|                              |                |    |  |
|------------------------------|----------------|----|--|
| Basic function               |                |    | Residual current circuit breakers                              |
| Number of poles              |                |    | 2 pole   |
| Application                  |                |    | Switchgear for industrial and advanced commercial applications |
| Rated current                | $I_n$          | A  | 125  |
| Rated short-circuit strength | $I_{cn}$       | kA | 10 with back-up fuse   |
| Rated fault current          | $I_{\Delta N}$ | A  | 0.1  |
| Type                         |                |    | Type G/A (ÖVE E 8601)  |
| Tripping                     |                | A  | Short time-delayed   |
| Product range                |                |    | FRCmM-125  |
| Sensitivity                  |                |    | Pulse-current sensitive  |
| Impulse withstand current    |                |    | Surge-proof, 3 kA  |
| Contact sequence             |                |    |  |

## Technical data

### Electrical

|  |                      |            |                                 |
|--|----------------------|------------|---------------------------------|
| Types conform to   |                      |            | IEC/EN 61008                    |
| Current test marks   |                      |            | As per inscription              |
| Tripping   |                      | A          | 10 ms delayed                   |
| Rated operating voltage  | $U_n$                | V AC       | 240/415                         |
| Rated frequency  | f                    | Hz         | 50                              |
| Limit values of the operating voltage  |                      |            |                                 |
| Test circuit   |                      | V AC       | 100 - 250                       |
| Rated fault current  | $I_{\Delta n}$       | mA         | 100                             |
| Sensitivity  |                      |            | Pulse-current sensitive         |
| Rated insulation voltage   | $U_i$                | V          | 400                             |
| Rated impulse withstand voltage  | $U_{imp}$            | kV         | 2.5                             |
| Rated short-circuit strength   | $I_{cn}$             | kA         | 10 with back-up fuse            |
| Impulse withstand current  |                      |            | 3 kA (8/20 $\mu$ s) surge-proof |
| Max. admissible back-up fuse   |                      |            |                                 |
| Short-circuit  | gG/gL                | A          | 125                             |
| Overload   | gG/gL                | A          | 80                              |
| Rated making and breaking capacity / Rated residual making and breaking capacity | $I_m / I_{\Delta m}$ | A          | 1250                            |
| lifespan   |                      |            |                                 |
| Electrical   |                      | Operations | 2000                            |
| Mechanical   |                      | Operations | 5000                            |

### Mechanical

|                          |  |    |    |
|--------------------------|--|----|----|
| Standard front dimension |  | mm | 45 |
| Device height            |  | mm | 80 |

|  |                 |  |
|--|-----------------|--|
| Built-in width                                 | mm              | 36                                     |
| Mounting                                       |                 | Quick attachment for DIN-rail EN 50022 |
| Degree of Protection                           |                 | IP20 switches<br>IP 40 enclosed        |
| Terminals top and bottom                       |                 | Twin-purpose terminals                 |
| Terminal protection                            |                 | Busbar tag shroud to BGV A3, ÖVE-EN 6  |
| Terminal cross-section                         |                 |  |
| Solid  | mm <sup>2</sup> | 1.5 - 50                               |
| Thickness of busbar material                   | mm              | 0.8 - 2                                |
| Admissible ambient temperature range           | °C              | -25 - +40                              |
| Permissible storage and transport temperatures | °C              | -25 - +60                              |
| Climatic proofing                              |                 | according to IEC/EN 61008              |
| Mounting position                              |                 | As required                            |
| Contact position indicator                     |                 | red / green                            |
| Trip indication                                |                 | toggle-center position                 |

## Design verification as per IEC/EN 61439

|  |                   |    |   |
|--|-------------------|----|---|
| Technical data for design verification                   |                   |    |   |
| Rated operational current for specified heat dissipation | I <sub>n</sub>    | A  | 125   |
| Heat dissipation per pole, current-dependent             | P <sub>vid</sub>  | W  | 0   |
| Equipment heat dissipation, current-dependent            | P <sub>vid</sub>  | W  | 18  |
| Static heat dissipation, non-current-dependent           | P <sub>vs</sub>   | W  | 0   |
| Heat dissipation capacity                                | P <sub>diss</sub> | W  | 0   |
| Operating ambient temperature min.                       |                   | °C | -25   |
| Operating ambient temperature max.                       |                   | °C | 60  |
|  |                   |    | Starting at 40 °C, the max. permissible continuous current decreases by 1.8% for every 1 °C |

## Technical data ETIM 6.0

|  |  |    |          |
|--|--|----|----------|
| Circuit breakers and fuses (EG000020) / Residual current circuit breaker (RCCB) (EC000003)   |  |    |          |
| Electric engineering, automation, process control engineering / Electrical installation, device / Residual current protection system / Residual current circuit breaker (RCCB) (ecl@ss8.1-27-14-22-01 [AAB906011]) |  |    |          |
| Number of poles  |  |    | 2        |
| Nominal rated voltage  |  | V  | 240      |
| Nominal rated current  |  | A  | 125      |
| Rated fault current  |  | A  | 0.1      |
| Mounting method  |  |    | DIN rail |
| Leakage current type   |  |    | A        |
| Selective protection   |  |    | No       |
| Short-circuit breaking capacity (I <sub>cw</sub> )   |  | kA | 10       |
| Surge current capacity   |  | kA | 3        |
| Frequency  |  |    | 50 Hz    |
| Additional equipment possible  |  |    | Yes      |
| Degree of protection (IP)  |  |    | IP20     |
| Construction size (in accordance with DIN 43880)   |  |    | 1        |
| Width in number of modular spacings  |  |    | 2        |
| Built-in depth   |  | mm | 70.5     |
| Short-time delayed tripping  |  |    | Yes      |

## Dimensions

