



Fuse-link, low voltage, 200 A, AC 500 V, D5, 56 x 46 mm, aR, DIN, IEC, ultra rapid

Article no. 200D200R
Catalog No. 200D200R

Similar to illustration

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	200
Rated voltage			AC 500 V
Construction size			D5
Size			56 x 46 mm
Utilization category			aR
Breaking Capacity		kA	50
usable for size/applications			for fuse-base R2
Release characteristic	class		ultra rapid
Standard/Approval			DIN IEC
Shape			bottle
Standards/Regulations			IEC 60269-3 VDE 0636

Technical data ETIM 6.0

Circuit breakers and fuses (EG000020) / D-system fuse link (EC000099)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Diazed fuse link (ecl@ss8.1-27-14-20-04 [AFZ799012])			
Construction size			DV
Nominal rated current		A	200
Nominal rated voltage		V	500
Colour code			Blue
Utilization category			aR (accompanied semiconductor protection)
Release characteristic			Super fast (FF)

Additional product information (links)

Product datasheet (pdf)	http://www.cooperbusmann.com/pdf/120f9a44-0f59-42bb-ae36-5b0e4eda6431.pdf
-------------------------	---