

**Fuse-link, LV, 20 A, AC 500 V, D1, aR, IEC, ultra rapid**



**Article no.**               **20D16R**  
**Catalog No.**           **20D16R**

Similar to illustration

### Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	20
Rated voltage			AC 500 V
Construction size			D1
Utilization category			aR
Breaking Capacity		kA	50
usable for size/applications			E16
Release characteristic	class		ultra rapid
Standard/Approval			IEC
Shape			bottle
Standards/Regulations			IEC 60269-3 VDE 0636

### Technical data ETIM 6.0

Circuit breakers and fuses (EG000020) / D-system fuse link (EC000099)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Diazed fuse link (ecl@ss8.1-27-14-20-04 [AFZ799012])			
Construction size			D1
Nominal rated current		A	20
Nominal rated voltage		V	500
Colour code			Blue
Utilization category			aR (accompanied semiconductor protection)
Release characteristic			Super fast (FF)

### Additional product information (links)

Product datasheet (pdf)	<a href="http://www1.cooperbusmann.com/pdf/89d39a2a-2145-4922-a1f3-087f5ab42c22.pdf">http://www1.cooperbusmann.com/pdf/89d39a2a-2145-4922-a1f3-087f5ab42c22.pdf</a>
-------------------------	---