



Fuse-link, LV, 40 A, AC 400 V, D02, gL/gG, IEC, time-delay

Article no. 40NZ02
Catalog No. 40NZ02

Similar to illustration

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	40
Rated voltage			AC 400 V
Construction size			D02
Utilization category			gL/gG
Breaking Capacity		kA	50
usable for size/applications			E18
Release characteristic	class		time-delay
Standard/Approval			IEC
Shape			bottle
Standards/Regulations			IEC 60269-3 VDE 0636

Technical data ETIM 6.0

Circuit breakers and fuses (EG000020) / D0-system fuse link (EC001642)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse systems / Neozed fuse link (ecl@ss8.1-27-14-21-19 [ACN353008])			
Construction size			D02
Nominal rated current		A	40
Nominal rated voltage		V	400
Colour code			Black
Utilization category			gL/gG (cable protection/equipment protection)

Additional product information (links)

Product datasheet (pdf)	http://www1.cooperbusmann.com/pdf/89d39a2a-2145-4922-a1f3-087f5ab42c22.pdf
-------------------------	---