



Fuse-link, low voltage, 40 A, AC 500 V, D3, gL/gG, DIN, IEC, time-delay

Article no. **40D33**
Catalog No. **40D33**

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	40
Rated voltage			AC 500 V
Construction size			D3
Utilization category			gL/gG
Breaking Capacity		kA	50
usable for size/applications			E33
Release characteristic	class		time-delay
Standard/Approval			DIN IEC
Shape			bottle
Standards/Regulations			IEC 60269-3 VDE 0636

Technical data ETIM 6.0

Circuit breakers and fuses (EG000020) / D-system fuse link (EC000099)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Diazed fuse link (ecl@ss8.1-27-14-20-04 [AFZ799012])			
Construction size			DIII
Nominal rated current		A	40
Nominal rated voltage		V	500
Colour code			Black
Utilization category			gL/gG (cable protection/equipment protection)
Release characteristic			Time-lag

Additional product information (links)

Product datasheet (pdf)	http://www.cooperbusmann.com/pdf/120f9a44-0f59-42bb-ae36-5b0e4eda6431.pdf
-------------------------	---