



**Fuse-link, LV, 80 A, AC 500 V, NH00, aM, IEC, dual indicator, live gripping lugs**

**Article no. 80NHM00B**  
**Catalog No. 80NHM00B**

Similar to illustration

## Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	80
Rated voltage			AC 500 V
Construction size			NH00
Utilization category			aM
Status indicator			dual (combination) indicator system
Description			live gripping lugs
Breaking Capacity		kA	120
Standard/Approval			IEC
Shape			square body with knife blade contacts
Standards/Regulations			IEC 60269-2 fuse system A DIN 43620 VDE 0636-2

## Technical data ETIM 6.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss8.1-27-14-20-05 [AFZ800012])			
Construction size			NH00
Nominal rated current		A	80
Nominal rated voltage		V	500
Utilization category			aM (switchgear protection)
Type of fuse status indicator			Combination fuse status indicator

## Additional product information (links)

Product datasheet (pdf)	<a href="http://www1.cooperbusmann.com/pdf/f41fff8f-6464-4cec-af1d-1ade033c2573.pdf">http://www1.cooperbusmann.com/pdf/f41fff8f-6464-4cec-af1d-1ade033c2573.pdf</a>
-------------------------	---