



Fuse-link, LV, 400 A, AC 500 V, NH2, aM, IEC, dual indicator, live gripping lugs

Article no. 400NHM2B
Catalog No. 400NHM2B

Similar to illustration

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	400
Rated voltage			AC 500 V
Construction size			NH2
Utilization category			aM
Status indicator			dual (combination) indicator system
Description			live gripping lugs
Breaking Capacity		kA	120
Standard/Approval			IEC
Shape			square body with knife blade contacts
Standards/Regulations			IEC 60269-2 fuse system A DIN 43620 VDE 0636-2

Technical data ETIM 6.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss8.1-27-14-20-05 [AFZ800012])			
Construction size			NH2
Nominal rated current		A	400
Nominal rated voltage		V	500
Utilization category			aM (switchgear protection)
Type of fuse status indicator			Combination fuse status indicator

Additional product information (links)

Product datasheet (pdf)	http://www1.cooperbusmann.com/pdf/f41fff8f-6464-4cec-af1d-1ade033c2573.pdf
-------------------------	---