



Fuse-base, LV, 250 A, AC 690 V, NH1, 3P, IEC, 185mm busbar spacing, M12 bolts

Article no. **BFD1-33-LL**
Catalog No. **BFD1-33/LL**

Similar to illustration

Delivery program

Product range			Fuse accessory
Basic function			Fuse-base
Field of application			low voltage
Rated current	I	A	250
Rated voltage			AC 690 V
Construction size			NH1
Description			185 mm busbar spacing M12 bolts
Number of poles			3P
Standard/Approval			IEC
Shape			vertical
Standards/Regulations			IEC

Technical data ETIM 6.0

Low-voltage industrial components (EG000017) / In-line fuse base (EC001046)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Fuse strip (ecl@ss8.1-27-37-14-02 [AKF059010])			
Model			Fuse switch disconnecter
Double interrupting			No
Rated permanent current I _u		A	250
Distance between rail centre, 40 mm			No
Distance between rail centre, 50 mm			No
Distance between rail centre, 60 mm			No
Distance between rail centre, 100 mm			No
Distance between rail centre, 185 mm			Yes
Max. rated operation voltage U _e AC		V	690
Conditioned rated short-circuit current I _q		kA	120
Type of electrical connection of main circuit			Rail connection
Number of poles			3
Construction size fuse insert			NH1