



Fuse-link, LV, 80 A, AC 400 V, D03, gL/gG, IEC, time-delay

Article no. **80NZ03**
Catalog No. **80NZ03**

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	80
Rated voltage			AC 400 V
Construction size			D03
Utilization category			gL/gG
usable for size/applications			for fuse-base M30 for domestic and general industrial applications
Release characteristic	class		time-delay
Standard/Approval			IEC
Standards/Regulations			IEC 60269-3 VDE 0636

Technical data ETIM 6.0

Circuit breakers and fuses (EG000020) / D0-system fuse link (EC001642)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse systems / Neozed fuse link (ecl@ss8.1-27-14-21-19 [ACN353008])			
Construction size			D03
Nominal rated current		A	80
Nominal rated voltage		V	400
Colour code			Silver
Utilization category			gL/gG (cable protection/equipment protection)

Additional product information (links)

Product datasheet (PDF)	http://www.cooperindustries.com/content/dam/public/bussmann/iec-electrical/resources/data-sheets/bus-iec-ds-4124-danddofuselinks.pdf
-------------------------	---