



Fuse-link, LV, 30 A, AC 500 V, D2, aR, IEC, ultra rapid

Article no. 30D27R
Catalog No. 30D27R

Similar to illustration

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	30
Rated voltage			AC 500 V
Construction size			D2
Utilization category			aR
usable for size/applications			E27 for domestic and general industrial applications
Release characteristic	class		ultra rapid
Standard/Approval			IEC
Standards/Regulations			IEC 60269-3 VDE 0636

Technical data ETIM 6.0

Circuit breakers and fuses (EG000020) / D-system fuse link (EC000099)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Diazed fuse link (ecl@ss8.1-27-14-20-04 [AFZ799012])			
Construction size			DII
Nominal rated current		A	30
Nominal rated voltage		V	500
Colour code			Black
Utilization category			aR (accompanied semiconductor protection)
Release characteristic			Super fast (FF)

Additional product information (links)

Product datasheet (PDF)	http://www.cooperindustries.com/content/dam/public/bussmann/iec-electrical/resources/data-sheets/bus-iec-ds-4124-danddofuselinks.pdf
-------------------------	---