



Fuse-link, low voltage, 100 A, AC 600 V, DC 300 V, 29 x 118 mm, J, UL, time-delay, with indicator

Article no. LPJ-100SPI
Catalog No. LPJ-100SPI

Similar to illustration

Delivery program

| | | | |
|------------------------|-------|----|--|
| Product range | | | Fuse |
| Basic function | | | Fuse-link |
| Field of application | | | low voltage |
| Rated current | I | A | 100 |
| Rated voltage | | | AC 600 V DC 300 V |
| Size | | | 29 x 118 mm |
| Utilization category | | | J |
| Status indicator | | | with indicator |
| Breaking Capacity | | kA | 300 |
| Release characteristic | class | | time-delay |
| Standard/Approval | | | UL |
| Time delay | | | time-delay 10 seconds (minimum) at 500% of rated current |

Technical data ETIM 6.0

| | | | |
|--|--|---|------------------------------|
| Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss8.1-27-14-20-05 [AFZ800012]) | | | |
| Construction size | | | - |
| Nominal rated current | | A | 100 |
| Nominal rated voltage | | V | 600 |
| Utilization category | | | - |
| Type of fuse status indicator | | | Centre fuse status indicator |

Additional product information (links)

| | |
|-------------------------|---|
| Product datasheet (pdf) | http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-b/Bus_Ele_DS_1007_LPJ_70-600.pdf |
|-------------------------|---|