



Fuse-link, low voltage, 200 A, AC 600 V, DC 300 V, 41 x 146 mm, J, UL, time-delay, with indicator

**Article no.** LPJ-200SPI  
**Catalog No.** LPJ-200SPI

Similar to illustration

## Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	200
Rated voltage			AC 600 V DC 300 V
Size			41 x 146 mm
Utilization category			J
Status indicator			with indicator
Breaking Capacity		kA	300
Release characteristic	class		time-delay
Standard/Approval			UL
Shape			cylindrical centre-bolted tags
Time delay			time-delay 10 seconds (minimum) at 500% of rated current

## Technical data ETIM 6.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss8.1-27-14-20-05 [AFZ800012])			
Construction size			-
Nominal rated current		A	200
Nominal rated voltage		V	600
Utilization category			-
Type of fuse status indicator			Centre fuse status indicator

## Additional product information (links)

Product datasheet (pdf)	<a href="http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-b/Bus_Ele_DS_1007_LPJ_70-600.pdf">http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-b/Bus_Ele_DS_1007_LPJ_70-600.pdf</a>
-------------------------	---