



Shutter for withdrawable unit IZMX164

Part no. IZMX-SH164-1
Article no. 184191
Catalog No. 67C2581G24

Delivery program

| | | |
|-------------------|--|---|
| Product range | | Accessories |
| Accessories | | Withdrawable units |
| Accessories | | Shutter |
| | | When the breaker is withdrawn from its connected position, the shutters automatically cover the cassette's live main terminals. |
| Pole | | 4 |
| For use with | | IZMX-CAS164... |
| | | for withdrawable unit |
| Installation type | | Withdrawable |

Design verification as per IEC/EN 61439

| | | |
|--|----|-----|
| Technical data for design verification | | |
| Operating ambient temperature min. | °C | -25 |
| Operating ambient temperature max. | °C | 70 |

Technical data ETIM 6.0

| | | |
|--|---|------|
| Low-voltage industrial components (EG000017) / Chassis part power circuit breaker (EC002043) | | |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Chassis part circuit breaker (ecl@ss8.1-27-37-04-22 [ACN955008]) | | |
| Rated current In | A | 1600 |
| Number of poles | | 4 |
| Version as busbar adapter | | No |
| Version as built-in device | | Yes |
| Type of electrical connection of main circuit | | - |