



Connections, front, 1600A, IZMX40, 3 p, fixed mounted design

Part no. IZMX-TF403-1600F-1
Article no. 184174
Catalog No. 67C2975H04

Delivery program

Product range			Accessories
Accessories			Main terminal kits
Accessories			Front connections
			This connection kit comes with front terminals for connection to the circuit-breaker. The circuit-breaker can be connected directly with CU bars on the rear flanged connection. If necessary, the optional front terminals can be installed before the circuit-breaker is installed in the enclosure. This way, the final connection to the circuit-breaker can be made from the front.
Rated current	I_n	A	800 - 1600
Pole			3
For use with			IZMX40...3...08F IZMX40...3...10F IZMX40...3...12F IZMX40...3...16F INX40...3...08F INX40...3...10F INX40...3...12F INX40...3...16F
Information about equipment supplied			Each set includes the connections for top and bottom. 3-pole for 6 connections, 4-pole for 8 connections Screws, washers, and supports are included as standard.
Installation type			Fixed

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	70

Technical data ETIM 6.0

Low-voltage industrial components (EG000017) / Connection vane/phase spreader (EC002019)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Connection vane/phase spreader (ec1@ss8.1-27-37-13-05 [ACN990009])			
Suitable for number of poles			3

Dimensions

