




Outdoors flush-mounting/hollow-wall model with the requested RAL color; form of delivery for projects

Part no. KLV-F3L-4PR-RAL*
Article no. 178894

Delivery program

Product image			
Basic function			Basic device
Product function			Installation distribution boards
Product range			KLV for projects
Design			Hollow wall Flush mounted
Installation site			Indoor
Type of installation			Hollow-wall mounting and flush mounting
Door/Flap			Desired color
Degree of Protection			IP30
Colour			Desired color
Shroud for protection against accidental contact			Plastic
Rows	Count		3
Module units per row			12
Description			IP30 Protection Class II Sheet steel door, desired color (RAL)
Equipment supplied			Door frame with door 3D adjustment element for mounting Installation instructions

Technical data

General

Standards			IEC/EN 60670-24
RoHS (in accordance with Directive 2002/95/EC of the European Parliament and Council)			conform
Ambient temperature		°C	-5 - +40
Degree of Protection			IP30
Rated frequency	f	Hz	50

Material characteristics

Material			Sheet steel, powder-coated
Colour			Desired color (RAL)

Material properties

Mechanical			
Impact resistance			IK05

Technical data ETIM 6.0

Distribution boards (EG000023) / Accessories for small distribution board (EC002287)		
Electric engineering, automation, process control engineering / Electrical installation, device / Electrical installation, device (accessories) / Accessories for small distribution board (ecl@ss8.1-27-14-92-45 [ADI499004])		
Type of accessory		-

Additional product information (links)

IL014009Z KLV Compact distribution board	
IL014009Z KLV Compact distribution board	ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL014009ZU2015_10.pdf
Product overview (Web)	http://www.eaton.eu/DE/Europe/Electrical/ProductsServices/Residential/index.htm

