

Flush-mounted wall trough 4-row; form of delivery for projects

Powering Business Worldwide*

Part no. KLV-UP4-4PR Article no. 178841

Similar to illustration

Delivery program

Don'tory program		
Product image		
Basic function		Basic device
Product function		Installation distribution boards
Product range		KLV for projects
Design		Flush mounted
Installation site		Indoor
Type of installation		Flush mounting
Door/Flap		White
Degree of Protection		IP30
Colour		White
Shroud for protection against accidental contact		Plastic
Rows	Count	4
Module units per row		12
Description		IP30 Protection Class II Plastic housing
Cable entries		Cable entries on top and bottom, side, back plate
Equipment supplied		Empty wall trough Spirit level for leveling Nail lugs Guard Gland plate slider Installation instructions

Technical data

General

Standards			IEC/EN 62208, IEC/EN 60670-24		
RoHS (in accordance with Directive 2002/95/EC of the European Parliament and Council)			conform		
Ambient temperature		°C	-5 - +40		
Degree of Protection			IP30		
Rated frequency	f	Hz	50		
Material characteristics					
Material			Polystyren (plastic)		
Colour			white (RAL 9016)		
Material properties					
Mechanical					
Impact resistance			IK05		

Technical data ETIM 6.0

Distribution boards (EG000023) / Accessories for small distribution board (EC002287)

Electric engineering, automation, process control engineering / Electrical installation, device / Electrical installation, device (accessories) / Accessories for small distribution board (ecl@ss8.1-27-14-92-45 [ADI499004])

Type of accessory -

Additional product information (links)

IL014007Z KLV compact distribution board

	-	
	IL014007Z KLV compact distribution board	ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL014007ZU2015_10.pdf
	Product overview (Web)	http://www.eaton.eu/DE/Europe/Electrical/ProductsServices/Residential/index.htm