



Fuse-link, LV, 1.25 A, AC 600 V, 10 x 38 mm, CC, UL, time-delay, rejection-type

Article no. LP-CC-1-1-4
Catalog No. LP-CC-1-1/4

Similar to illustration

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	1.25
Rated voltage			AC 600 V
Size			10 x 38 mm
Utilization category			CC
Description			rejection-type
Breaking Capacity		kA	200
Release characteristic	class		time-delay
Standard/Approval			UL
Shape			cylindrical
Time delay			time-delay 12 seconds (minimum) at 200% of rated current

Technical data ETIM 6.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss8.1-27-14-20-02 [AFZ797010])			
Size			10x38 mm
Rated voltage			AC 600 V
Nominal current		A	1.25
With striker			No

Additional product information (links)

Product datasheet (PDF)	http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-b/Bus_Ele_DS_1023_LP-CC.pdf
-------------------------	---