



Fuse-link, LV, 1.8 A, AC 600 V, 10 x 38 mm, CC, UL, time-delay, rejection-type

**Article no.** LP-CC-1-8-10  
**Catalog No.** LP-CC-1-8/10

Similar to illustration

## Delivery program

|                        |       |    |  |
|------------------------|-------|----|--|
| Product range          |       |    | Fuse   |
| Basic function         |       |    | Fuse-link  |
| Field of application   |       |    | low voltage  |
| Rated current          | I     | A  | 1.8  |
| Rated voltage          |       |    | AC 600 V   |
| Size                   |       |    | 10 x 38 mm   |
| Utilization category   |       |    | CC   |
| Description            |       |    | rejection-type   |
| Breaking Capacity      |       | kA | 200  |
| Release characteristic | class |    | time-delay   |
| Standard/Approval      |       |    | UL   |
| Shape                  |       |    | cylindrical  |
| Time delay             |       |    | time-delay 12 seconds (minimum) at 200% of rated current |

## Technical data ETIM 6.0

|  |  |   |          |
|--|--|---|----------|
| Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)  |  |   |          |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss8.1-27-14-20-02 [AFZ797010]) |  |   |          |
| Size   |  |   | 10x38 mm |
| Rated voltage  |  |   | AC 600 V |
| Nominal current  |  | A | 1.8      |
| With striker   |  |   | No       |

## Additional product information (links)

|                         |   |
|-------------------------|---|
| Product datasheet (PDF) | <a href="http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-b/Bus_Ele_DS_1023_LP-CC.pdf">http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-b/Bus_Ele_DS_1023_LP-CC.pdf</a> |
|-------------------------|---|