



Fuse-link, LV, 32 A, AC 690 V, NH000, gL/gG, IEC, dual indicator, insulated gripping lugs

Article no. **32NHG000BI-690**
Catalog No. **32NHG000BI-690**

Delivery program

| | | | |
|-----------------------|---|----|--|
| Product range | | | Fuse |
| Basic function | | | Fuse-link |
| Field of application | | | low voltage |
| Rated current | I | A | 32 |
| Rated voltage | | | AC 690 V |
| Construction size | | | NH000 |
| Utilization category | | | gL/gG |
| Status indicator | | | dual (combination) indicator system |
| Description | | | insulated gripping lugs |
| Breaking Capacity | | kA | 120 |
| Standard/Approval | | | IEC |
| Shape | | | square body with knife blade contacts |
| Standards/Regulations | | | IEC 60269-2 fuse system A DIN 43620 VDE 0636-2 |

Technical data ETIM 6.0

| | | | |
|--|--|---|---|
| Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss8.1-27-14-20-05 [AFZ800012]) | | | |
| Construction size | | | NH000 |
| Nominal rated current | | A | 32 |
| Nominal rated voltage | | V | 690 |
| Utilization category | | | gL/gG (cable protection/equipment protection) |
| Type of fuse status indicator | | | Combination fuse status indicator |

Additional product information (links)

| | |
|-------------------------|---|
| Product datasheet (pdf) | http://www1.cooperbusmann.com/pdf/0df538ca-460e-4185-b185-4aa9277ce71b.pdf |
|-------------------------|---|