

Article no. **M-NITD16**
Catalog No. **M-NITD16**

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	16
Rated voltage			AC 550 V
Construction size			BS88/A1
Size			14 x 55 mm
Utilization category			gL/gG
Breaking Capacity		kA	80
usable for size/applications			general industrial applications
Standard/Approval			BS IEC
Shape			offset bolted tags (slotted)
Standards/Regulations			BS88-2 IEC 60269-2
Optional accessories			fuse-holder RS20 CM32FC

Technical data ETIM 6.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss8.1-27-14-20-05 [AFZ800012])			
Construction size			-
Nominal rated current		A	16
Nominal rated voltage		V	550
Utilization category			gL/gG (cable protection/equipment protection)
Type of fuse status indicator			None

Additional product information (links)

Product datasheet (pdf)	http://www1.cooperbusmann.com/pdf/55199884-b399-4f18-9e88-f430faca44d8.pdf
-------------------------	---