

Article no. **M-NITD32**
Catalog No. **M-NITD32**

Delivery program

| | | | |
|------------------------------|---|----|---------------------------------|
| Product range | | | Fuse |
| Basic function | | | Fuse-link |
| Field of application | | | low voltage |
| Rated current | I | A | 32 |
| Rated voltage | | | AC 550 V |
| Construction size | | | BS88/A1 |
| Size | | | 14 x 55 mm |
| Utilization category | | | gL/gG |
| Breaking Capacity | | kA | 80 |
| usable for size/applications | | | general industrial applications |
| Standard/Approval | | | BS IEC |
| Shape | | | offset bolted tags (slotted) |
| Standards/Regulations | | | BS88-2 IEC 60269-2 |
| Optional accessories | | | fuse-holder RS20 CM32FC |

Technical data ETIM 6.0

| | | | |
|--|--|---|---|
| Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss8.1-27-14-20-05 [AFZ800012]) | | | |
| Construction size | | | - |
| Nominal rated current | | A | 32 |
| Nominal rated voltage | | V | 550 |
| Utilization category | | | gL/gG (cable protection/equipment protection) |
| Type of fuse status indicator | | | None |

Additional product information (links)

| | |
|-------------------------|---|
| Product datasheet (pdf) | http://www1.cooperbusmann.com/pdf/55199884-b399-4f18-9e88-f430faca44d8.pdf |
|-------------------------|---|