



**N/N terminal with plug-in connection for EWK enclosure; 6x1.5-16mm<sup>2</sup>  
+21x0.75-4mm<sup>2</sup>**



Powering Business Worldwide™

**Part no. NN-EWK**  
**Article no. 178515**

## Delivery program

|                      |  |  |                         |
|----------------------|--|--|-------------------------|
| Basic function       |  |  | Accessory consideration |
| Accessories          |  |  | EWK                     |
| Product range        |  |  | EWK DB0                 |
| Degree of Protection |  |  | IP2X                    |

## Technical data ETIM 6.0

|   |  |                 |                    |
|---|--|-----------------|--------------------|
| Terminal blocks (EG000012) / Ground terminal block (EC000901)   |  |                 |                    |
| Electric engineering, automation, process control engineering / Electrical installation, device / Clamp (not overhead line) / Ground terminal block (ecl@ss8.1-27-14-11-41 [AKE269011]) |  |                 |                    |
| PEN function possible   |  |                 | No                 |
| Connectable conductor cross section fine-strand without cable end sleeve  |  | mm <sup>2</sup> | 25 - 25            |
| Connectable conductor cross section fine-strand with cable end sleeve   |  | mm <sup>2</sup> | 16 - 16            |
| Connectable conductor cross section solid-core  |  | mm <sup>2</sup> | 0.76 - 25          |
| Connectable conductor cross section multi-wired   |  | mm <sup>2</sup> | 25 - 25            |
| Type of electrical connection 1   |  |                 | Screw connection   |
| Type of electrical connection 2   |  |                 | Plug-in connection |
| Connection position   |  |                 | Inclined           |
| Number of levels  |  |                 | 1                  |
| Number of clamp positions per level   |  |                 | 27                 |
| Mounting method   |  |                 | Direct mounting    |
| Material insulation body  |  |                 | Thermoplastic      |
| Operation temperature   |  | °C              | 5 - 35             |
| Inflammability class of insulation material acc. with UL94  |  |                 | V0                 |
| Width/grid dimension  |  | mm              | 5                  |
| Height at lowest possible mounting height   |  | mm              | 5                  |
| Length  |  | mm              | 190                |
| Closing plate required  |  |                 | No                 |
| Colour  |  |                 | -                  |

## Additional product information (links)

|                        |   |
|------------------------|---|
| Product overview (Web) | <a href="http://www.eaton.eu/DE/Europe/Electrical/ProductsServices/Residential/index.htm">http://www.eaton.eu/DE/Europe/Electrical/ProductsServices/Residential/index.htm</a> |
|------------------------|---|