

**Article no.** M-NSD4  
**Catalog No.** M-NSD4

## Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	4
Rated voltage			AC 550 V
Construction size			BS88/F1
Size			14 x 59 mm
Utilization category			gL/gG
Breaking Capacity		kA	80
usable for size/applications			general industrial applications
Standard/Approval			BS IEC
Shape			offset bladed tags
Standards/Regulations			BS88-2 IEC 60269-2
Optional accessories			fuse-holder 32NNS and SC32

## Technical data ETIM 6.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss8.1-27-14-20-05 [AFZ800012])			
Construction size			-
Nominal rated current		A	4
Nominal rated voltage		V	550
Utilization category			gL/gG (cable protection/equipment protection)
Type of fuse status indicator			None

## Additional product information (links)

Product datasheet (pdf)	<a href="http://www1.cooperbusmann.com/pdf/f1780856-8d9e-4fab-8cc8-1b803cf5c0d0.pdf">http://www1.cooperbusmann.com/pdf/f1780856-8d9e-4fab-8cc8-1b803cf5c0d0.pdf</a>
-------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------