



Fuse-link, LV, 100 A, AC 500 V, BS88, 21 x 95 mm, gL/gG, BS

**Article no.** OSD100  
**Catalog No.** OSD100

## Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	100
Rated voltage			AC 500 V
Construction size			BS88
Size			21 x 95 mm
Utilization category			gL/gG
Breaking Capacity		kA	80
usable for size/applications			general industrial applications
Standard/Approval			BS
Shape			offset bolted tags
Standards/Regulations			BS88 IEC 60269
Optional accessories			fuse-holder CM100F

## Technical data ETIM 6.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss8.1-27-14-20-05 [AFZ800012])			
Construction size			-
Nominal rated current		A	100
Nominal rated voltage		V	500
Utilization category			gL/gG (cable protection/equipment protection)
Type of fuse status indicator			None

## Additional product information (links)

Product datasheet (pdf)	<a href="http://www1.cooperbusmann.com/pdf/2cd86bf0-5229-43c1-a84a-b3f642e4a2a9.pdf">http://www1.cooperbusmann.com/pdf/2cd86bf0-5229-43c1-a84a-b3f642e4a2a9.pdf</a>
-------------------------	---