

Drive shaft, 6 mm, for P1, P3, L = 340 mm

Part no. P1/P3-M400
Article no. 172844

Delivery program

Product range			Accessories
Part group reference			P1 P3
Basic function			shaft extensions
			Steel
Notes			Handle SVB(-SW)-P3/M (172841; 172843) not in combination with Neutral Switch N-P3Z (64805).
Shaft diameter			6 x 6
Shaft length		mm	340
For use with			P1.../M... P3.../M...

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	50

Technical data ETIM 6.0

Low-voltage industrial components (EG000017) / Accessories for low-voltage switch technology (EC002498)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Low-voltage switch technology (accessories) / Component for low-voltage switch technology (accessories) (ecI@ss8.1-27-37-92-01 [AKN570010])			
Type of accessory			-

Additional product information (links)

IL008007ZU P1-.../XM, P3-.../XM, P1-.../M4..., P3-.../M4...	
IL008007ZU P1-.../XM, P3-.../XM, P1-.../M4..., P3-.../M4...	ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL008007ZU2016_07.pdf
Form for ordering non-standard front plates	http://ecat.moeller.net/flip-cat/?edition=HPLEN&startpage=4.87
Technical overview cam switch, switch-disconnector	http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&startpage=4.2
System overview cam switch T	http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&startpage=4.4
System overview switch-disconnector P	http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&startpage=4.6
Key to part numbers Cam switch	http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&startpage=4.8
Key to part numbers Switch-disconnector	http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&startpage=4.8
Switches for ATEX	http://www.coopercrouse-hinds.eu/en/products/25-ex-safety-and-main-current-switches.html